

Street Approach/Culvert Permit Application

Submit application and drawings to applications@crossroadstx.gov.

Applicant's Name:						
Last			First		Middle	
Owner's Name:						
	Last		First		Middle	
Mailing Address:						
	Street		City	State	Zip Code	
Applicant Email	Address					
Property Owner Em	nail Addre	SS				
Applicant's Phone	Number:					
		Home	Work		Mobile	
Owner's Phone Number:						
		Home	Work		Mobile	
Contact Name:			Phone#:			
Length of culvert inc	ludina dan	ad has drugling				
Length of curvent me	ruanig stop	bed fieldwalls.				
Location Description	n:					
Distance from side	property	lines:				
Number of culvert pe	ermits need	led:				
			Office Use			
Date Requested		Date Issued		Rec. Clerk		
Date Inspected		Inspector				
Check #		Receipt #				

3201 US HWY 380 Suite 105 Cross Roads, TX 76227 940-365-9693 CrossRoadsTX.gov



Guidelines for Installing a Street Approach/Culvert

- 1. The Culvert Application is good for 60 days if it is a culvert application only.
- 2. New construction. The culvert will need to be complete before a Certificate of Occupancy can be issued. A temporary culvert has to be in place at the same time the first inspection is called for.
- 3. The permit applicant will mark the proposed location of the culvert by two stakes or flags and have the sloped headwalls formed and readied for cement before inspection. **INSPECTION MUST BE REQUESTED BEFORE** <u>THE POURING OF THE HEADWALLS.</u>
- 4. The culvert must be placed in the flow line of the ditch.
- 5. The minimum culvert size is 15-inch diameter.
- 6. The minimum culvert driving surface width off a Town road is 15 feet.
- 7. The culvert shall have soil composition covering the culvert of either a minimum 3 ¹/₂" of hard surface cover or 6" of ground road base materials.
- 8. All culverts must have concrete safety ends. A concrete safety end is to be sloped with a minimum ratio of 4:1 length culvert diameter and a minimum 1-foot-wide perimeter around the edge of the sloped end.
- 9. A road transition tie in, is required where driveway meets Town Road e.g., no gap between driveway and road pavement. If the driveway is constructed of concrete, there must be a 12" asphalt area between the edge of the road pavement and the concrete.
- 10. The permit issued by the Town of Cross Roads must be posted by the area so that the inspector can sign off on it.
- 11.Certificate of Occupancy will not be issued until inspection of culvert has been approved.

3201 US HWY 380 Suite 105 Cross Roads, TX 76227 940-365-9693 CrossRoadsTX.gov